


Product Code

9740/RA6

Electrical Actuator
100Nm 230V 50/60Hz



POLYHEDRA

CLASSIC

Product use

Actuators can be assembled, using suitable flanged adaptors, to 2-ways ball valves and to manual 3-ways ball valves. They are assembled directly on the motorized 3-ways ball valves. Once this coupling has been performed, the valve can be opened or closed remotely. Alternatively, the actuator can be excluded and the valve can be operated manually.

Castel manufactures actuator with a variety of operational characteristics: they are manufactured with a synthetic, self-extinguishing housing that covers the motor, the control and cut-out electronics based on the gear reducer torque and the self centring fixing system of the valve rod.

In the event of a power outage to the actuator, the gear reducer can be disengaged using the specific lever, to permit manual use of the valve.

Furthermore, auxiliary contacts for switching are available for remote control of the valve status.

Product details

Tensione [V]	230
Frequenza [Hz]	50/60
Potenza [W]	45
Grado di protezione	IP 66
Angolo di manovra	90°
Coppia [Nm]	100
Tempo di marcia [sec]	120

Temperatura ambiente [°C] min. -10

Temperatura ambiente [°C] max. +55

Adatto per rubinetto a sfera vedere gli accoppiamenti indicati nella tabella SCHEMA ACCOPPIAMENTI

Confezione n° pz 1

Notes

(1) Conessioni elettriche : uscita in commutazione a 2 punti (aperto/chiuso) oppure uscita in continua (0 ÷ 10V)

(2) Conessioni elettriche : uscita in commutazione a 2 punti (aperto/chiuso)

(3) Conessioni elettriche : uscita in continua (0 ÷ 10V)