



Product Code

9120/RD3

Coil Type HM3
220-230V 50/60Hz



Product use

Coils with the new ?FAST LOCK? fixing system, series 9300 and 9320, and coils with gear fixing systems, series 9110, 9120 and 9160.

Fast-on connections type DIN 43650/A for coils in series: 9120, 9160, 9300 and 9320; co-moulded cables for series 9110 coils. Protection rating IP65; IP68 for series 9160 coils coupled with series 9155 connectors. Available voltages; 24 VAC - 50/60 Hz, 110 VAC - 50/60 Hz, 220/230 VAC - 50/60 Hz, 240 VAC - 50/60 Hz, 380 VAC - 50/60 Hz, 12 VDC, 24 VDC, 27 VDC, 48 VDC.

Connectors in series 9150, normalized DIN 43650, to wire, with IP65 protection rating. Connectors in series 9900, again normalized DIN 43650, pre-wired with various cable lengths, with IP65 protection rating. Connectors in series 9155, to wire, with IP65/68 protection rating.

Product details

Desenho img(9120_RA6.jpg)

Tipo de Bobina HM3 (1)

N° catálogo 9120/RD3

N° catálogo

Tensão [V] 27 D.C.

Frequência [Hz] -

Potência [W] 20

Comprimento do cabo [m] -

Notes

- (1) bobina com peça sobressalente G9150/R97 (anel amarelo + parafuso preto + OU)
- (2) Use exclusivamente com conector retificador 9150/R45