


Product Code

SF412/5A

CLASSIC



Product use

Dryers for the liquid line that allow the replacement of the dryer elements, so-called cartridges. Accessories for use with the following ASHRAE 34:2019 refrigerants, Class A1:

HCFC (R22)

HFC (R134a, R404A, R407C, R410A, R507)

HFO (R1234ze)

HFO + HFC (R448A, R449A, R450A, R452A, R513A, R515A, R515B)

Product details

Desenho img(4411_5A.jpg)

N° catálogo SF412/5A

Conexões ODS Ø [in.] 5/8"

Conexões ODS Ø [mm] 16

Tipo de cartucho 4490/A4490/B4490/AA4490/AB4490/BA4490/BB

N° cartucho 2

Cubo nominal [cm³] 1600

PS[bar] 47

MWP [psi] (1) 600

TS[°C] min. -40

TS[°C] max. +80

Embalagem 1

Castel non si assume alcuna responsabilità per eventuali errori nei cataloghi, opuscoli e altro materiale stampato o indicato nel sito Castel.it. Castel si riserva il diritto di modificare i propri prodotti senza preavviso. Tutti i marchi in questo materiale sono di proprietà di Castel. Tutti i diritti riservati.

Castel assumes no responsibility for any errors in catalogs, brochures and other material printed or indicated on the Castel.it website. Castel reserves the right to modify its products without notice. All trademarks in this material are the property of Castel. All rights reserved.

Notes

(1): em conformidade com a aprovação UL