

Product Code


3350/5S

Receiver Pressure Regulator

5/8"-16mm ODS

PS = 28 bar - 405 PSI

CLASSIC



Product use

These regulators are used with condensing pressure regulators, instead of differential valves. Together, these valves form a control system that maintains constant condenser and liquid receiver tank pressure in systems with heat recovery and air and water condensation. They by-pass the hot gas from the compressor outlet to the liquid receiver tank, increasing the pressure of the liquid in the receiver tank.

Accessories for use with the following ASHRAE 34:2019 refrigerants, Class A1:

HCFC (R22)

HFC (R134a, R404A, R407C, R410A, R507)

HFO (R1234ze)

HFO + HFC (R448A, R449A, R450A, R452A, R513A, R515A, R515B)

Product details

Desenho 

N° catálogo 3350/5S

Conexões SAE Flare -

Conexões Ø ODS [in.] 5/8"

Ø ODS [mm] 16

Campo de regulação [bar] 3 - 20

Kv [m³/h] 1,8

PS [bar] 28

MWP [psi] (1) 406

Castel non si assume alcuna responsabilità per eventuali errori nei cataloghi, opuscoli e altro materiale stampato o indicato nel sito Castel.it. Castel si riserva il diritto di modificare i propri prodotti senza preavviso. Tutti i marchi in questo materiale sono di proprietà di Castel. Tutti i diritti riservati.

Castel assumes no responsibility for any errors in catalogs, brochures and other material printed or indicated on the Castel.it website. Castel reserves the right to modify its products without notice. All trademarks in this material are the property of Castel. All rights reserved.

TS [°C] min.	- 40
TS [°C] max.	+ 110
Embalagem	15

Notes

(1): em conformidade com a aprovação UL