


Product Code

7690N/M12

Vibration Absorber
12mm ODS



Product use


Accessories for use with the following ASHRAE 34:2019 refrigerants, Class A1, A2L, or A3:

- HFC (R134a, R32, R404A, R407C, R410A, R507)
- HFO and HFO/HFC blends (R1234ze, R1234yf, R448A, R449A, R450A, R452A, R452B, R454B, R513A)
- HC (R290, R600, R600a, R1270)

Maximum allowable pressure PS = 50 bar.

Allowable temperatures TS = -80 to +140 °C

AISI 304 stainless steel connections.



Product details

Desenho img(7690N_3.jpg)

N° catálogo 7690N/M12

Conexões ODS Ø [in.] -


Conexões ODS Ø [mm] 12

PS [bar] TS [°C]-80 / +100 50

PS [bar] TS [°C]+120 49

TS [°C]+150 48

Embalagem 100



Castel non si assume alcuna responsabilità per eventuali errori nei cataloghi, opuscoli e altro materiale stampato o indicato nel sito Castel.it. Castel si riserva il diritto di modificare i propri prodotti senza preavviso. Tutti i marchi in questo materiale sono di proprietà di Castel. Tutti i diritti riservati.

Castel assumes no responsibility for any errors in catalogs, brochures and other material printed or indicated on the Castel.it website. Castel reserves the right to modify its products without notice. All trademarks in this material are the property of Castel. All rights reserved.

