



Product Code

1028EX/3A6

Solenoid Valve ATEX

3/8"ODS 220-230V

PS = 50 bar

POLYHEDRA

Product use

Solenoid valves with the "EX" suffix are compliant with the ESR of Directive 2014/34/EU "ATEX". This equipment is suitable for use on refrigeration systems located in areas classified as "Zone 2" risk of explosion, according to the definition in Annex I of Directive 1999/92/EC.

Accessories for use with the following ASHRAE 34:2019 refrigerants, Class A1, A2L, or A3:

HFC (R134A, R32, R404A, R407C, R410A, R507)

HFO (R1234YF, R1234ZE)

HFO + HFC (R448A, R449A, R450A, R452A, R452B, R454A, R454B, R454C, R455A, R513A, R515A, R515B)

HC (R290, R600, R600A, R1270)

These valves are only sold in the model with the ATEX certified coil (A6 suffix).

Product details

Princípio de funcionamento	Ação direta
Desenho	img(1028EX_2A6.jpg)
N° catálogo	1028EX/3A6
Tipo de Bobina (1)	HM2(EX)
Ligações ODS Ø [in.]	3/8"
Ligações ODS Ø [mm]	-
Kv [m³/h]	0,23
PS [bar]	50

TS [°C] min.	-40
TS [°C] max.	+130
Embalagem	24

Notes

(1) : Bobinas montadas nas válvulas