



Product Code

1098EX/7A6

Solenoid Valve ATEX
7/8"-22mm ODS 220-230V
PS = 50 bar

POLYHEDRA

Product use

Solenoid valves with the "EX" suffix are compliant with the ESR of Directive 2014/34/EU "ATEX". This equipment is suitable for use on refrigeration systems located in areas classified as "Zone 2" risk of explosion, according to the definition in Annex I of Directive 1999/92/EC.

Accessories for use with the following ASHRAE 34:2019 refrigerants, Class A1, A2L, or A3:

HFC (R134A, R32, R404A, R407C, R410A, R507)

HFO (R1234YF, R1234ZE)

HFO + HFC (R448A, R449A, R450A, R452A, R452B, R454A, R454B, R454C, R455A, R513A, R515A, R515B)

HC (R290, R600, R600A, R1270)

These valves are only sold in the model with the ATEX certified coil (A6 suffix).

Product details

Princípio de funcionamento Servocomandocom membrana

Desenho img(1098EX_5A6.jpg)

N° catálogo 1098EX/7A6

Tipo de Bobina (1) HM2(EX)

Ligações ODS Ø [in.] 7/8"

Ligações ODS Ø [mm] 22

Kv [m³/h] 5,7

PS [bar] 50

TS [°C] min.	-40
TS [°C] max.	+120
Embalagem	14

Notes

(1) : Bobinas montadas nas válvulas